

## Product Description



Product performance:

- 1) standard SATA - 13 pin (6 + 7) drive interface, support for SATA - I/SATA - / SATA II - III standard. Support the highest transmission rate 6 GBPS.
- 2) support Window2K / 2003 / XP/Vista / 7, Linux, Mac OS 10.
- 3) support the standard 2.5 -inch SATA hard disk, suitable for 9.0 mm / 9.5 mm drive SATA interface.

Specification:

1. Shell material: Plastic
2. Colour: black, white, and blue
3. Interface: SATA TO SATA
4. Operating frequency: 50 to 60 hz
5. Power supply: 5 v / 1 a
6. Power: 5 w (maximum)
7. Working temperature: 0 to 30 °C
8. Product size: 130 \* 127 \* 9.0 mm

Installation method:

1. installing the hard disk to the hard drive bracket.
2. Paralelly insert hard disk interface into the end bracket.
3. Fixing screws on the both sides of disk brackets into the hard disk.

## Product Picture





  
Fragile

  
Do not  
drop

  
Avoid  
contact  
with  
magnet

CE   
RoHS



Fragile

Do not drop

Avoid contact with magnet

CE  
RoHS





Fragile

Do not drop

Avoid contact with magnet

CE RoHS



SATA 2nd HDD  
Caddy

