Product Description

1) Working frequency: 50 to 60 hz
2) Power supply: 5 v / 1 a
3) Power: 5 w (maximum)
4) Working temperature: 0 to 30 ℃
5) Shell material: aluminum alloy
1Height9mm
2interface:SATA(ODD) -13Pin (6+7)(HDD) ,Supports SATA - I/SATA - / SATA II - III standard.Support the highest transmission rate 6 GBPS. 3Bezel:can meet the original.
4Size(L*W*H):130*127*9mm
5Same as the common optical driver
6HDD support:2.5-inch notebook hard drive with SATA or SATA
7Compatible Model:New models of HP, DELL, ACER, BenQ, Asus, Lenovo, Great Wall and all the IDE drive interfaces (9mm) machine are applicable
8Following models are confirmed
9supported perfectly by this bracket: Asus F8VA. Samsung R518. Toshiba dynabook tx/66hbl.HP6535b.HP6930p.HASEEA560
10Accessories
1 * 9mm SATA 2nd HDD Caddy
1 * Screwdriver
4 * Screws
11Notes Hard Drive, Bezel and DVD Drive are Not Included
12Warranty 12 Months
13Condition 100% Brand New
Certificate CE RoHS FCC

Product Picture


Laptop 2nd HDD Frame
Installation method
1
2
3
4
Note:
To avoid the damage, pls don't squeeze the HDD when make the installation
HDD

SERIAL ATA
Installation method
1
2
3
4
Note :
To avoid the damage, pls don't squeeze the HDD when make the installation
MADE IN CHINA
HDD

HD9001-SS

use 2.5" SSD
or HDD
2nd HDD Caddy
Insert HDD or SSD into drive caddy
and secure at bottom with the
4 screws provided
Insert caddy with HDD (or SSD)
in optical drive bay