

Product Description



- 1) Working frequency: 50 to 60 hz
 - 2) Power supply: 5 v / 1 a
 - 3) Power: 5 w (maximum)
 - 4) Working temperature: 0 to 30 °C
 - 5) Shell material: aluminum alloy
 - 1) Height 9mm
 - 2) interface: SATA(ODD) -13Pin (6+7)(HDD) ,Supports SATA - I/SATA - / SATA II - III standard.Support the highest transmission rate 6 GBPS. 3) Bezel:can meet the original.
 - 4) Size(L*W*H):130*127*9mm
 - 5) Same as the common optical driver
 - 6) HDD support:2.5-inch notebook hard drive with SATA or SATA
 - 7) Compatible Model:New models of HP, DELL, ACER, BenQ, Asus, Lenovo, Great Wall and all the IDE drive interfaces (9mm) machine are applicable
 - 8) Following models are confirmed
 - 9) supported perfectly by this bracket: Asus F8VA. Samsung R518. Toshiba dynabook tx/66hbl.HP6535b.HP6930p.HASEEA560
 - 10) Accessories
 - 1 * 9mm SATA 2nd HDD Caddy
 - 1 * Screwdriver
 - 4 * Screws
 - 11) Notes Hard Drive, Bezel and DVD Drive are Not Included
 - 12) Warrantly 12 Months
 - 13) Condition 100% Brand New
- Certificate CE RoHS FCC

Product Picture













Insert HDD or SSD into drive caddy
and secure at bottom with the
4 screws provided



Insert caddy with HDD (or SSD)
in optical drive bay

