

## Product Description



Adaptateur secteur pour ordinateur portable pour HP 18,5 v 3.5 a 65W 4,8 x 1,7 mm jaune

Entrée (Input): 100-240V (universel)

Sortie (output): tension: 18,5 v courant: 3.5 a

Puissance (puissance): 65W

Interface: 4,8 x 1,7 mm

HP Compaq NC4010

Série de Compaq Armada

110/e500/E500s/E700/M300/M700/V300

Série Compaq Presario

2800/2800CA/2800t/2800us/2801CL/2805US/x/X1015/X1015US/X1030/X1030US/X1040/X1040US

Série Compaq evo

Evo N1000C, evo N1000V, evo N1005V, evo Notebook N1000C, evo Notebook N1000V

N110/N150/N200/N400c/N410c/N600/N600c/N610c/N620c/N800/N800c/N800v/N800w

Caractéristiques:

1. protection de court-circuit de sortie
2. filtre de protection contre les surtensions de surcharge
3. l'utilisation de composants importés, fiabilité élevée
4. bonne capacité d'anti-brouillage
5. ondulation de c.c, rendement élevé
6. basse température, longue durée de vie
7. la gamme de tension d'entrée large, en conformité avec la norme mondiale
8. bonnes propriétés d'isolation, force diélectrique élevée
9. court-circuit, surcharge, protection contre les surtensions
10. pleine charge de combustion à haute température, 100% essai de combustion

## Product Picture





hp  
WATL0AE7XWSIU (REV. A01) 65W HP Power Adapter  
HP Power Adapter (Part of the HP Laptop)  
HP Power Adapter (Part of the HP Laptop)  
HP Power Adapter (Part of the HP Laptop)  
HP Power Adapter (Part of the HP Laptop)

CAUTION: DO NOT OPEN FOR REPAIRS  
Do not open the power adapter for repair. Opening the power adapter may void the warranty and create a fire hazard.  
Do not touch the power adapter when it is plugged into a power source. The power adapter may become hot.  
Do not use the power adapter with a damaged power cord or plug. A damaged power cord or plug may create a fire hazard.  
Do not use the power adapter with a damaged power source. A damaged power source may create a fire hazard.  
Do not use the power adapter with a damaged power outlet. A damaged power outlet may create a fire hazard.  
Do not use the power adapter with a damaged power cable. A damaged power cable may create a fire hazard.

INPUT: 100-240V ~ 1.6A/1.6A 50-60Hz  
OUTPUT: 12.5V (1.9V) ~ 3.5A (3.5A) LPS  
EFFICIENCY LEVEL: Ⓢ

Rev:A01 65W  
9869344114

CT: WATL0AE7XWSIU





