## Product Description

Product performance:

1)standard SATA - 13 pin (6 + 7) drive interface, support for SATA - I/SATA - / SATA II - III standard.Support the highest transmission rate 6 GBPS.

2) support Window2K / 2003 / XP/Vista / 7, Linux, Mac OS 10.

3) support the standard 2.5 -inch SATA hard disk, suitable for 9.0 mm / 9.5 mm drive SATA interface.

Specification:

1.Shell material:: Plastic
2.Colour: black, white, and blue
3.Interface: SATA TO SATA
4.Operating frequency: 50 to 60 hz
5.Power supply: 5 v / 1 a
6.Power: 5 w (maximum)
7.Working temperature: 0 to 30 ℃
8.Product size: 130 * 127 * 9.0 mm

Installation method:

1.installing the hard disk to the hard drive bracket.
2.Paralelly insert hard disk interface into the end bracket.
3.Fixing screws on the both sides of disk brackets into the hard disk.

## Product Picture

Fragile
Do not drop
Avoid contact with magnet
CE
RoHS

Fragile
Do not drop
Avoid contact with magnet
CE
RoHS

Fragile
Do not drop
Avoid contact with magnet
CE
RoHS

Second HDD Caddy
SATA 2nd HDD Caddy
HDD/SSD
SATA-III
SERIAL
ATA
RoHS