



Product parameter

Product information at a glance



Product name:: Travel adapter

Product model:	HHT907	Socket current ::	10A
Rated voltage:	100-250V	Socket material :	PC(fireproof material)
Conductive material:	phosphor bronze	Product certification :	CE FCC ROHS
Pin type: US standard, CHN standard, EU standard, UK standard, AUS standard			

Single-port output:

USB C1 Output:5.0V/3.0A,9.0V/3.0A,12.0V/3.0A,15.0V/3.0A,20.0V/3.25A(65W Max)
USB C2/C3 Output: 5.0V/3.0A,9.0V/2.22A,12.0V/1.67A(20W Max)
USB A1/A2 Output: 5.0V/3.0A,9.0V/2.0A,12.0V/1.5A(18W Max)

Two-port output:

USB C1+C2或C3 Output:45W+20W;
USB C1+ USB A1或A2 Output:45W+18W;
USB C2+C3或USB A1或USB A2 Output :5.0V/3.0A (15W Max)
USB A1+A2 Output: 5.0V/3.0A (15W Max)

Three-port output:

USB C1+C2+C3 Output:45W+15W
USB C1+USB A1+A2 Output:45W+15W
USB C2+USB C3+USB A1 Output: 5.0V/3.0A (15W Max)
USB C3+USB A1+A2 Output: 5.0V/3.0A (15W Max)

Quad output:

USB C1+C2+C3+USB A1或A2 Output:45W+15W
USB C2+C3+USB A1+A2 Output:5.0V/3.0A(15W Max)

Five-port output:

USB C1+C2+C3+USB A1+A2 Output:45W+15W





Model: HHT807
Input: 100V-240V~50/60HZ
Fuse Rating: 10A
Power: MAX 1000W at 100V, MAX 2400W at 240V
Total DC Output: 65W
Retractable cable USB-C1 Output: 5.0V/3.0A, 9.0V/3.0A,
12.0V/3.0A, 15.0V/3.0A, 20.0V/3.25A (65W Max)
USB-C2/C3 Output: 5.0V/3.0A, 9.0V/2.22A, 12.0V/1.67A (20W Max)
USB-A1/A2 Output: 5.0V/3.0A, 9.0V/2.5A, 12.0V/1.5A (18W Max)
Made in China

QC18W PD20W

65W GaN

**Multifunctional in one,
small and practical**

**65W high power
Charging laptop**



